



8809, Large LED Display Temp. + RH% Datalogger

- Wall mountable super large display for easy reading and save space
- Air temp., dew point temp.& RH% display
- Tripod mountable receptacle for long time use
- Detachable standers to transform as desktop
- Recording temp. & humidity for quality control
- Button and PC programing are both available
- Several methods to start recording: schedule/immediately start/key start/ repeat start
- Recording function must be powered by adaptor
- Monitoring mode is powered by adaptor
- Built in USB interface for program & down load
- LED flash & audible warning while exceeding threshold
- Up to 16000 points memories
- Temperature units switchable
- Salt bottle self-calibration available
- Features: red LED display.

Model	8809
Air temp. range	-20~70°C
Air temp. Resolution	0.1°C(0.1°F)
Air temp. accuracy	±0.6°C (0~50°C), others ±1.2°C
Humidity range	0%RH ~ 100%RH
Humidity resolution	0.1%RH
Humidity accuracy	±3%RH (at 25°C, 10~90%RH others ±5%RH)
Sampling points	16000
Buttton to on/off	Yes
USB interface	Yes
LCD size (mm)	51(H)x63(W)
Storage temp.	-20~50°C
Storage RH%	Humidity <90%
Dimension(mm)	120x93x42
Meter Weight	~210g
Battery	Only 9VDC adaptor (No Batteries)
Standard Package	Meter, adaptor, manual, paper box, software CD, USB cable.
Optional Accessory	RH calibration salt kit.