



More information on the website
radwag.com/en/info,w1,DMO

PMV 50 PLUS Moisture Analyzer



Functions



Drying modes



Samples drying



Moisture content analysis



Dry mass determination



Microwave drying

Datasheet

Metrological parameters

Maximum capacity [Max]	50 g
Readability [d]	0,1 mg
Tare range	-50 g
Adjustment	external
Maximum sample weight	50 g
Heating module	microwave radiation emitter
Moisture content readability	0,0001%

Physical parameters

Display	5,7" resistive colour touchscreen
---------	-----------------------------------

Physical parameters	
Packaging dimensions	670×510×570 mm
Protection class	IP 43
Weighing pan material	glass fibre filter ø 90 mm
Communication interface	
Communication interface	RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100-240 V AC 50/60 Hz ¹
Heating module power	800 W
Environmental conditions	
Operating temperature	+10 ÷ +40 °C
Features of use	
Finish mode	4 modes (automatic, manual, time-defined, user-defined)

¹ 100-130 V AC 50/60 Hz (version A)

200-240 V AC 50/60 Hz (version B)

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Receipt Printer
Granite Antivibration Tables
Barcode scanners
Moisture analyzer accessories

Balance Storage Case
RS 232, RS 485 cables
RS 232 – USB Converter
RS 232 cables (scale - EPSON printer)

Software

RAD-KEY
E2R System

LabVIEW Driver
RADWAG Development Studio

Device dimensions

