

Auto range

SOUND LEVEL METER

Model : SL-4012

ISO-9001, CE, IEC1010



Auto range, AC output, Memory

DIGITAL SOUND LEVEL METER

Model : SL-4012

FEATURES

| | |
|---|--|
| * Large LCD display, easy to read. | * Hold & Memory record (max., min.) |
| * Frequency weighting networks are designed to meet IEC 61672 type 2. | * Condenser microphone for high accuracy & stability. |
| * Auto range & manual range. | * Peak Hold function for stored the maximum value. |
| * A & C weighting networks are conformity to standards. | * Warning indicator for over and under load. |
| * Fast & Slow dynamic characteristic modes. | * LCD display for low power consumption & clear read-out even in bright ambient light condition. |
| * AC output for system expansion. | * Used the durable, long-lasting components, including a strong light weight ABS-plastic housing case. |
| * RS232 computer interface. | * Compact and light weight plastic housing. |
| * Build in adj. VR is available for easy calibration. | |

SPECIFICATIONS

| | |
|---------------------------------|---|
| Display | 52 mm x 32 mm LCD (Liquid Crystal Display), 5 digits. |
| Function | dB (A & C frequency weighting), Time weighting(Fast, Slow), Hold, Memory (max. & min.), Peak hold, AC & RS232 output. |
| Measurement Range | 30 - 130 dB. |
| Resolution | 0.1 dB. |
| Accuracy (23 5 蚓) | Frequency weighting meet IEC 61672 type 2, calibrating input signal on 94 dB(31.5 Hz to 8 kHz), then the accuracy of A weighting is specified as following: 31.5 Hz - ± 3 dB, 63 Hz - ± 2 dB, 125 Hz - ± 1.5 dB 250 Hz - ± 1.5 dB, 500 Hz - ± 1.5 dB, 1 kHz - ± 1.5 dB, 2kHz - ± 2 dB, 4 kHz - ± 3 dB, 8 kHz - ± 5 dB. |
| Frequency Weighting Network | Characteristics of A & C. A weighting - The characteristic is simulated as "Human Ear Listing" response. Typical, if making the environmental sound level measurement, always select to A weighting. C weighting - The characteristic is near the "FLAT" response. Typical, it is suitable for checking the noise of machinery (Q.C. check) & knowing the sound pressure level of the tested equipment. |
| Frequency | 31.5 Hz to 8,000 Hz. |
| Calibrator | B & K (Bruel & kjaer), multi-fuction acoustic calibrator, model : 4226. |
| Microphone | Electric condenser microphone. |
| Size of microphone | 1/2 inch standard size. |
| Range selector | Auto range : 30 to 130 dB. Manual range : 3 range, 30 to 80 dB, 50 to 100 dB, 80 to 130 dB, 50 dB on each step, with over & under range indicating. |
| Time Weighting (Fast & Slow) | Fast - $t = 200$ ms, Slow - $t = 500$ ms, * "Fast" range is simulated the human ear response time weighting. "Slow" range is easy to get the average values of vibration sound level. * The "Fast" & "Slow" time weighting range are designed to IEC 651 type 2 requirement. |
| Output Signal | * AC output - AC 0.5 Vrms corresponding to each range step. Output impedance - 600 ohm. * RS232 output. |
| Out terminal | Terminal 1 : RS232 computer interface terminal. Terminal 2 : AC output terminal. * Terminal socket size : 3.5 mm dia. phone socket. |
| Calibration VR | Build in external calibration VR, easy to calibrate on 94 dB level by screw driver. |
| Operating Temp. | 0 °C to 50 °C (32°F to 122°F). |
| Operating Humidity | Less than 80% RH. |
| Power Supply | 006P DC 9V battery (Alkaline or heavy duty type). |
| Power Consumption | Approx. DC 6mA. |
| Dimension | 268 x 68 x 29 mm (10.6 x 2.7 x 1.1 inch). |
| Weight | 295 g/0.65 LB. |
| Standard Accessories | Instruction Manual1 PC. |
| Optional | Sound Calibrator, model : SC-941 (94 dB). SC-942 (94dB, 114 dB). Carrying case : CA-06 RS232 cable, Model : UPCB-02 Application software, Model : SW-U801-WIN |

* Appearance and specifications listed in this brochure are subject to change without notice.