



# Solar Simulation Systems - 500 Watt

## Solar Simulation Systems

### SS100AAA - 500 Watt Solar Simulator

#### SS100AAA-TP TOUCH PANEL SYSTEM



Please click on image for a larger view.

#### FEATURES:

- Light intensity feedback for stable light output intensity
- Computer based Controller
- Manual / automatic shutter control
- External lamp alignment with lamp on
- Manual/Automatic/External/Remote shutter control
- Forced air cooling
- Lamp life display
- Selectable and adjustable constant intensity or constant lamp current
- Safety Interlock override warning
- Shutter Status Indicator
- Lamp status indicator
- Remote Trouble Shooting via Internet
- One (1) year factory warranty

## **SS100AAA-EM ELECTRO-MECHANICAL SYSTEM**



Please click on image for a larger view.

## FEATURES:

- Light intensity feedback for stable light output intensity
- Electro-Mechanical Controller
- Lamp life display
- External lamp alignment with lamp on
  
- Manual/Automatic/External/Remote shutter control
- Forced air cooling
- Lamp Life Meter
- Lamp Current Meter
- Selectable and adjustable constant intensity or constant power mode
- Safety Interlock override LED
- Over Temperature Warning LED
- Shutter Status Indicator
- Lamp status indicator
- One (1) year factory warranty

**SS100AAA-TP & SS100AAA-EM TECHNICAL SPECIFICATIONS**

Feature Description	Specification
Type of Lamp	Xenon Short Arc
Lamp Power	500W
Max. Illuminated Area	3.94" (100mm) x 3.94" (100mm)
Light Source	Steady State
Air Mass	AM1.5G Standard: AM1.5D or AM1 optional
Lamp lifetime	1500 Hours
Adjustment Range of Light Intensity	100mW/cm <sup>2</sup> ±15%
Simulator Class*	AAA
Spectral Match to all intervals*	±25% or better
Spatial Non-uniformity of irradiance*	≤ 2% or better
Short Term Temporal Instability (STI)*	≤ 0.5% or better
Long Term Temporal Instability (LTI)*	≤ 2% or better
Dimensions (Height x Width x Depth)	50.6" (1,285mm) x 14.5" (368mm) x 20.8" (529mm)
Weight	65 Lbs. (29.5 Kg)
The Optimum Working Distance	9.4" (239 mm)
Phase/Voltage/Frequency	Single Phase/110-220AC Volts/50-60Hz
Max. Power Consumption (W)	1.0 KVA

\*Meets Class A Requirements of ASTM E927-2010, IEC60904-9 Edition 2.0 2007-10 and JIS C 8912-1998: amendment 1-2005 & Amendment 2-2011

Specifications are subject to change without notice



[SiteMap](#) | [Privacy Policy](#)

[Terms & Conditions](#)

[Home](#)

[About Us](#)

[Our Distributors](#)

[Products](#)

[Technical Documentation](#)

[Contact Us](#)

[Tradeshows & Events](#)

## Contact Info

6085 King Drive Unit 104  
Ventura, CA 93003

Phone: (805) 482-5200  
Fax: (805) 482-5252  
[pet@photoemission.com](mailto:pet@photoemission.com)

© Photo Emission Tech, Inc. 2022 | Built by MK